

Petefoth SailfishOS: Bluetooth in Android AppSupport

Pete documents his solutions to allowing android apps (the lxc container) bluetooth access in his repo:

<https://codeberg.org/petefoths-projects/SfOS-Bluetooth-in-AAS/>

or

<https://codeberg.org/poetaster/SfOS-Bluetooth-in-AAS>

Implementation of a method in SailfishOS (SfOS) to allow user to switch Bluetooth (BT) support between SfOS and Android AppSupport (AAS).

Current status

As stated in [this forum post](#)

“ I have something similar working using `qCommand` app: switching BT to AAS is working fine; switching it back to SfOS is still ‘work-in-progress’ - sometimes it works, sometimes not.

Current status of my `qCommand` stuff. (For both commands I've commented out the `if systemctl is-active` condition, because it's not working as expected)

`qc_BT-to-Android` : mostly works. I can connect to and sync my watch in the Garmin Connect Android app, and connect to and control my hearing aids in the BeMore Android app.

Code

```

if [[ ! $(whoami) = "root" ]]; then
echo "must be run as root" >&2
exit 1
fi

# start by setting up the config file,even if it exists already
echo "[Config]" > /opt/appsupport/etc/appsupport.conf.d/99-passthrough.conf
echo
"Proxies=android.hardware.bluetooth@1.1::IBluetoothHci,android.hardware.bluetooth@1.0::IBluetoothHci/default" >> /opt/appsupport/etc/appsupport.conf.d/99-passthrough.conf

# Stop the BT services in SfOS
systemctl stop bluetooth
systemctl stop bluebinder

# Start AAS if it isn't running already:
# returns 3 if inactive
# 0 if active
if [[ ! $(systemctl is-active --quiet appsupport@defaultuser.service) = 0 ]]; then
echo "starting appsupport"
systemctl reload-or-restart appsupport@defaultuser
fi

# Start the Android BT process
appsupport-attach pm enable com.android.bluetooth

```

qc-BT-to-SfOS: mostly works. Occasionally gives an error when starting `bluebinder` times out. (I haven't checked the status of BT in SfOS if the error occurs. Nor have I looked into detail in "journalctl -xe". That, and sorting out the operations conditional on `systemctl is-active` are the next jobs :slight_smile:

Code

```

if [[ ! $(whoami) = "root" ]]; then
echo "must be run as root" >&2
exit 1
fi

```

```
# If AAS is running, stop / disable its BT process
#if [[ $(systemctl is-active --quiet appsupport@defaultuser.service) = 0 ]]; then
echo "DisablingBT in Android"
  appsupport-attach pm disable com.android.bluetooth
echo "Stopping AAS"
  systemctl stop appsupport@defaultuser
#fi

# Start the BT services in SfOS
echo "Starting bluebinder"
systemctl start bluebinder
echo "Starting AAS"
systemctl start appsupport@defaultuser
echo "Restarting bluetooth"
systemctl restart bluetooth
```

Occasional error

Job for bluebinder.service failed because a timeout was exceeded.
See "systemctl status bluebinder.service" and "journalctl -xe" for details.`

Background

The means to allow BT access for Android apps running under AAS is described in [this post in the SfOS communtiy forum](#). As described in that post and replies, BT can be available EITHER to SfOS OR to AAS, but not to both. The aim of this project is to proved a means for users to switch BT availability between SfOS and AAS.

Use cases

My use cases:

1. Garmin Smartwatch: download golf course data from Garmin Connect Android app running on the phone. As far as I know, this is the only way to achieve this: it is not possible to download Golf Course data from PC to watch. (Note this is a multi-sport watch and golf courses **are not** pre-loaded: they must be loaded from the phone. For dedicated Golf watches, with courses preloaded, course updates **can** be downloaded from PC or

Web)

2. [BeMore Hearing Aid control app](#). Proprietary Android app that allows fine-grained control of hearing aids - volume, noise filters, favourite settings

These operations are both short in duration: the workflow would be

1. Enable BT in AAS
2. Perform the operation
3. Disable BT in AAS and re-enable it in SfOS

The proposed solution would also meet the needs of users who wish to have BT access available to AAS

1. all the time: never available to SfOS
2. for as long as AAS is running

Implementation

I think this solution can be implemented by

1. Creating two shell scripts:
 - `bt-to-aas.sh` enables BT in AAS
 - `bt-to-sfos.sh` enables BT in SfOS
2. Implementing a mechanism to call these scripts from the SfOS UI

Enable BT in AAS (`bt-to-aas.sh`)

1. stop AAS if it is running - (is this doable from a script?). Or leave it running while we do steps 2 & 3, and **restart** AAS in step 4
2. stop bluetooth and bluebinder services
3. add (or uncomment) this line (using `sed`?) to `/opt/appsupport/etc/appsupport.conf.d/10-hybris.conf`
`Proxies=android.hardware.bluetooth@1.1::IBluetoothHci,android.hardware.bluetooth@1.0::IBluetoothHci/default`
4. start (or restart) AAS - (is this doable from a script, rather than from SfOS settings menu)

Enable BT in SfOS (`bt-to-sfos.sh`) I am less sure about what is needed here. A 'quick and dirty' solution might be to edit the `10-hybris.conf` file then reboot the phone. I would prefer a slightly more elegant and less destructive solution :slight_smile:

1. do I need to stop bluetooth and bluebinder services again, or are they still not still not running since being stopped in the `bt-to-aas.sh` script?

2. stop AAS

1. is this necessary or can we just restart it once we have changed the `10-hybris.conf` file?
2. is this: do-able from a script ?
3. OR disable AAS Android Bluetooth package, but leave AAS running
4. remove (or comment) this line(using `sed` ?) to `/opt/appsupport/etc/appsupport.conf.d/10-hybris.conf`
`Proxies=android.hardware.bluetooth@1.1::IBluetoothHci,android.hardware.bluetooth@1.0::IBluetoothHci/default`
5. restart bluetooth bluebinder and services
6. restart AAS (optional: we could leave this to be done manually)

Problems to solve

How to stop

- AAS if running: normally do this from from SFOS settings menu. Can we do it via a script?
- Stop bluetooth and bluebinder services: Solved in forum post

```
“ systemctl stop bluetooth  
systemctl stop bluebinder
```

How to change the contents of `10-hybris.conf`?

- o answer probably involves `sed`. I need to experiment to find out how to
 1. add the needed line in `10-hybris.conf`
 2. remove the added line in `10-hybris.conf`
- Better approach: don't touch `10-hybris.conf`, use a different file.
 - o Delete it to enable BT in SfOS
 - o Create it to enable BT in AAS

```
“ `echo  
"Proxies=android.hardware.bluetooth@1.1::IBluetoothHci,android.hardware.bluetooth@1.0::IBluetoothHci/default" > /opt/appsupport/etc/appsupport.conf.d/99-passthrough.conf
```


Where in the device filesystem will the scripts live? And how will they get there?

##

How to invoke the scripts so that they have root / `devel-su` access to perform privileged operations (e.g. starting / stopping `systemd` services)?

- answered [in SfOS forum](#)

“ You can run scripts as root by using qCommand app or Sailcron (at selected time). Scripts which don't need root are possible to run from launcher by creating *.desktop file. Scripts which don't need root are possible to run from launcher by creating *.desktop file.

Both our scripts will need root I think

Revision #2

Created 3 January 2026 21:12:48 by poetaster

Updated 5 January 2026 10:07:47 by poetaster